



## PLATING SERVICES SUMMARY

**Method:**

Overall continuous electroplating of strip coil stock including dual gauge (milled edge) and pre-stamped flat coil strip.

**Materials Plated:**

Copper, Copper Alloys, Steel, Stainless Steel.

**Plating:**

- **100% Tin:** Bright and Matte finish up to 12.50 in. wide.
- **Nickel:** Matte finish up to 9.00 in. wide.
- **Copper:** Matte finish to 12.50 in. wide.

**Underplating:**

- **Copper:** Copper/copper alloys, steel and stainless steel to 12.50 in. wide.
- **Nickel:** Copper, copper alloys, steel & stainless steel to 9.00 in. wide.
- **Wood's nickel:** Steel and stainless steel to 12.50 in. wide.

**Size Range:**

Coil size up to 50 in. diameter incoming and 52 in diameter outgoing,  
 Strip widths from approx. 0.25 to 12.50 in. wide. Call for widths below 0.25 in.  
 Inside Diameter (ID) Incoming: 8 to 20 in.  
 Inside Diameter (ID) Outgoing: 6, 12, 16 & 20 in.

General width, gauge and hardness guidelines.

Width Range	Gauge Range	Hardness
.25 - .99	.003 - .090+	
1.0 - 8.0	.003 - .064	.003 - .008 1/2 hard or harder. .046 - .090+ 1/2 hard or softer.
8.01-12.50	.007 - .040	.007 - .010 1/2 hard or harder.

Paper interleaf capability: Standard 12# bleached or paper supplied by customer  
 Plating Thickness: Per customer specifications.  
 Skid/Coil weight: Up to 6,000 pounds max.

An ISO 9001:2015 Certified Company

Selective Plating Inc. 240 South Lombard Road Addison IL Tel 630-543-1380

[www.SelectivePlatingInc.com](http://www.SelectivePlatingInc.com)



## PLATING PRODUCTS

### FINISH PLATING

**TIN:** A ductile, non-toxic metal generally used to improve corrosion resistance and maintain solderability of the base metal.

Matte Acid Tin (RoHS compliant)

Whitish/grey matte surface appearance. Softer than bright tin. Larger grain size and lower internal stress than bright tin. 99.98+ percent Tin. Compatible with lead-free and leaded solders. Better solderability than bright tin. Rougher surface finish and higher coefficient of friction than bright tin.

Bright Acid Tin (RoHS compliant)

Shiny/bright surface appearance. Harder than matte tin. Smaller grain size and relatively higher internal stress deposit than matte tin. 99.8+ percent Tin. Compatible with lead-free and leaded solders. Smoother surface finish and lower coefficient of friction than matte tin.

*Specifications: ASTM B545 Type I (Electrodeposited), MIL-T-10727*

**NICKEL:** Used to provide a decorative, wear resistant, corrosion resistant and anti-tarnishing surface with high temperature resistance.

Matte (Ductile) Nickel

Compliant with ASTM B689 Type 1 bath requirements. Provides a highly ductile deposit.

*Specifications: ASTM B689, QQ-N-290*

**COPPER:** A ductile metal used as a decorative finish or to provide improved conductivity.

Matte Copper

Our standard copper under-plate can also be applied as a finish plate. An anti-tarnish agent is applied to inhibit corrosion.

*Specifications: ASTM B734, MIL-C-14550*

An ISO 9001:2015 Certified Company

Selective Plating Inc. 240 South Lombard Road Addison IL Tel 630-543-1380

[www.SelectivePlatingInc.com](http://www.SelectivePlatingInc.com)



## PLATING PRODUCTS (Cont'd)

### UNDER-PLATING

**COPPER:** Applied under tin or nickel to improve ductility and adhesion of finish plating during part formation. Required to inhibit zinc migration (diffusion barrier) per ASTM B545 on certain alloys.

**NICKEL (SULFAMATE):** An optional solution to inhibit zinc migration (diffusion barrier) per ASTM B545. Can also be used to reduce stresses in tin plating (believed to play an important role in whisker formation) caused by the formation of the inter-metallic bond with copper alloys.

**NICKEL (WOODS FLASH):** Used as a preparatory layer to provide adhesion to stainless steel and nickel-bearing alloys.

### ASTM SPECIFICATIONS FOR PLATING ANODE METALS

TIN	B339
NICKEL	B39
COPPER	B170

An ISO 9001:2015 Certified Company

Selective Plating Inc. 240 South Lombard Road Addison IL Tel 630-543-1380

[www.SelectivePlatingInc.com](http://www.SelectivePlatingInc.com)

221206



## PLATING PRODUCTS / MATERIAL MATRIX

Customer Base Metal	Underplate	Plating	Width (Max.)
Copper and Copper Alloys	Nickel Flash/Copper	Tin (Bright, Matte)	12.50"
	Copper and/or Sulfamate Nickel	Tin (Bright, Matte), Nickel (Matte)	9.00"
Stainless Steel, Nickel-bearing Alloys & Cold-Rolled Steel	Woods Nickel Flash and Sulfamate Nickel	Tin (Bright, Matte), Nickel (Matte)	9.00"
Stainless Steel, Nickel-bearing Alloys & Cold-Rolled Steel	Woods Nickel Flash	Copper (Matte) and/or Tin (Bright, Matte)	12.50"

An ISO 9001:2015 Certified Company

Selective Plating Inc. 240 South Lombard Road Addison IL Tel 630-543-1380

[www.SelectivePlatingInc.com](http://www.SelectivePlatingInc.com)